

Greenland 30

Type	Tufted synthetic grass carpet	
Material	62% PE Monofilament straight & 38% PP Monofilament curled (UV Stabilized)	
Yarn quality	Environmental friendly, free of lead and cadmium	
Primary backing	100% PP black with fleece, UV Stabilized, Weight 142 gr/m ²	
Secondary backing	Black Latex compound with a base of styrenebutadiene (SBR), with drainage holes, Weight 684 gr/m ²	
Waterpermeability	60 liter/min/m ²	
Pile height	30 mm	± 2 mm
Face weight	955 gr/m ²	± 10%
Total weight	1.781 gr/m ²	± 10%
Tuft gauge	5/16 gauge	
Stitches per 10 cm linear	18	± 1%
Stitches per m²	22.680	± 10%
Colour	Mix of light and dark green + Field-Jute thatch	
UV stability	Meets DIN 53387 Standard (6000 hours)	
Colour fastness	Xenon Test: Blue Scale > 7, Grey-scale > 4	
Colour lining	Not Applicable	
Roll width	200 cm, 400 cm	
Roll length	20-25m	
Applications	Gardens, Landscaping, Terraces	
Infill advice	Silica sand, gradation 0,5 - 1,0 mm, 80% roundshaped, appr. 6 - 8 kg/m ²	
Comments	Before installation make sure the rolls are from the same production code (first 6 digits of the roll number) Project.	





Condor Group has the right to alter each product specification at any time to improve the carpet according to the most technological applications. Condor Group is not legally liable in case of non-compliance with the above mentioned specifications. The above mentioned specifications are for reference, and can only be used informally. The appearance of the final artificial grass carpet may change when it reaches temperatures beyond 70°C.