


CERTIFICATION AND CLASSIFICATION			Premium
Type of flooring	EN ISO 26986		Expanded (cushioned) polyvinyl chloride floor covering
CE certification			yes
Classification	ISO 10874 (EN 685)	 23  31	Residential: 23 Commercial: 31
TECHNICAL CHARACTERISTICS			Premium
Extreme protection PUR reinforcement			yes
Total thickness	ISO 24346 (EN 428)		3,20 mm
Wear layer thickness	ISO 24340 (EN 429)		0,30 mm
Total weight	ISO 23997 (EN 430)		2,30 kg/m ²
Form of delivery - Rolls	ISO 24341 (EN 426)		28 lm (15 - 28 lm) x 2,5/3/3,5 m 25 lm (15 - 25 lm) x 4 m
Wear layer binder content			Type 1
TECHNICAL PERFORMANCES			Premium
Dimensional stability	ISO 23999 (EN 434)		Requirement by standard: < 0,4 % Tarkett result: ≤ 10,011 %
Reaction to fire	EN 13501-1		Bfl - s1
Residual indentation	ISO 24343-1 (EN 433)		≤ 0,35 mm
Impact sound reduction	ISO 717/2		16 dB
Underfloor heating			Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance			Does not contribute to infection spreading
Castor chair test	ISO 4918 (EN 425)		Excellent
Light fastness	ISO 105 B02 - Method 3		≥ 6
Thermal resistance	EN 12524		0,04 - 0,05 m ² K/W

