

## Rauma GC

|                                          |                                        |                      |
|------------------------------------------|----------------------------------------|----------------------|
| <b>Manufacturing process</b>             | Tufted                                 | ISO 2424             |
| <b>Gauge</b>                             | 1/8" Cutpile                           |                      |
| <b>Fibre composition</b>                 | 100% PP                                |                      |
| <b>Primary backing</b>                   | Woven                                  |                      |
| <b>Backing</b>                           | GC                                     | ISO 2424             |
| <b>Total fibre weight of use surface</b> | 250 gr/m <sup>2</sup>                  |                      |
| <b>Total weight</b>                      | 810 gr/m <sup>2</sup>                  | +/- 15% ISO 8543     |
| <b>Pile height</b>                       | 4,0 mm                                 | ISO 1766             |
| <b>Total height</b>                      | 7,0 mm                                 | +15% / -10% ISO 1765 |
| <b>Tufts per 10cm</b>                    | 27                                     |                      |
| <b>Tufts per m<sup>2</sup></b>           | 86000                                  |                      |
| <b>Colour fastness to light</b>          | > 7                                    | ISO 105-B02          |
| <b>Roll width</b>                        | 100 cm, 133 cm, 200 cm, 300 cm, 400 cm |                      |
| <b>Application</b>                       | Landscaping                            |                      |
| <b>Comments</b>                          | UV stable for 3000 hours               |                      |

## Floorsymbols



## Certificates

ISO 9001:2015-certified processes  
 ISO 14001:2015-certified processes

2025-01-27