

QUALITY
ORDER CODE

DATE: **26/01/2024**
REPLACES: 22/09/2023

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM ✓
LIVING ROOM ✓
OFFICE ✓
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER
GUT-NUMBER
DIBT

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

SCALA ENDURANCE SB
SED

± 400
COLLECTION
1/10" CUT PILE

SOLUTION DYED

PP

WOVEN SYNTHETIC SECONDARY BACKING

± 1.000
± 2.320

± 5,5
± 8,5
± 197.000
± 39,40
± 50,00

± 33,0/13,0
±

± 30
PILE IN

✓
✓
✓

NO SHOCK
✓
✓

Cl. 23 / Cl. 32
Domestic Heavy / Commercial General
Tested on underlay



LC3

Efl

LOW RADIUS

Heavy contract / Extra-Heavy domestic

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 30



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

± 0,02

(±)

250Hz

± 0,04

(±)

500Hz

± 0,09



(±)

1000Hz

± 0,3

(±)

2000Hz

± 0,4

(±)

4000Hz

± 0,46

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

± 0,2

THERMAL RETENTION

(±) m²K/W

ISO 8302

± 0,072



TOG rating

(±)

± 0,72

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE R_{oT}

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE R_{dT}

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5



RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SB 400	SED
0100	RUBY - L 19,83 - ρ 2,95*
0110	CARMINE - L 25,57 - ρ 4,60*
0200	CHOCOLATE - L 18,49 - ρ 2,63*
0250	MAGNOLIA - L 59,91 - ρ 28,02*
0600	PINE - L 19,09 - ρ 2,77*
0700	NAVY - L 21,73 - ρ 3,44*
0800	EBONY - L 14,60 - ρ 1,83*
0820	SLATE - L 37,24 - ρ 9,67*
* Light Reflectance Value (L: CIE Lab - ρ: Rhô)	

SB 400	SED
(8)	



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE