

QUALITY  
ORDER CODE

DATE: **26/01/2024**  
REPLACES: 22/09/2023

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (±) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM ✓  
LIVING ROOM ✓  
OFFICE ✓  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER  
GUT-NUMBER  
DIBT

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

**SCALA MARATHON SB**  
**SMT**

± 400  
COLLECTION  
1/10" CUT PILE

SOLUTION DYED

PP

WOVEN SYNTHETIC SECONDARY BACKING

± 1.000  
± 2.320

± 5,5  
± 8,5  
± 197.000  
± 39,40  
± 50,00

± 15,0/10,0  
±

± 30  
PILE IN

✓  
✓  
✓

NO SHOCK  
✓  
✓

Cl. 23 / Cl. 32  
Domestic Heavy / Commercial General  
Tested on underlay



LC3

Efl

LOW RADIUS

Heavy contract / Extra-Heavy domestic

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 30



SOUND ABSORPTION

(±)

$\alpha_s$

ISO 354 - 125 Hz

± 0,02

(±)

250Hz

± 0,04

(±)

500Hz

± 0,09



(±)

1000Hz

± 0,3

(±)

2000Hz

± 0,4

(±)

4000Hz

± 0,46

SOUND ABSORPTION

(±)

$\alpha_w$

EN ISO 11654

± 0,2

THERMAL RETENTION

(±) m²K/W

ISO 8302

± 0,072



TOG rating

(±)

± 0,72

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE R<sub>oT</sub>

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE R<sub>dT</sub>

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5



RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SB 400	SMT
0100	RUBY - L 27,40 - ρ 5,24*
0110	CARMINE - L 32,47 - ρ 7,30*
0700	NAVY - L 30,43 - ρ 6,41*
0820	SLATE- L 42,37 - ρ 12,74*
* Light Reflectance Value (L: CIE Lab - ρ: Rhô)	

SB 400	SMT



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(4)