

STABIL LF

Manufacturing process	Needlefelt	ISO 2424
Surface aspect	Flat	ISO 2424
Dimensions	200 cm, 400 cm	
Backing	LF	ISO 2424
Pile yarn composition	100% PP	
Pile weight	900 g/m ²	
Total weight	1090 g/m ²	+/- 10% ISO 8543
Total height	5,2 mm	+/- 10% ISO 1765
Overall use class	Commercial 33, Areas with heavy use	EN 1307
Luxury class	LC1	EN 1307
Castor chair suitability	Yes, permanent use	EN 985
Stair suitability	Yes, permanent use	EN 1307
Colour fastness to light	≥ 5	ISO 105-B02
Colour fastness to rubbing, wet and dry	≥ 4	ISO 105-X12
Colour fastness to water	≥ 4	ISO 105-E01
Dimensional stability	Shrinkage ≤ 1,2 %	ISO 2551
	Extension ≤ 0,5 %	ISO 2551
Electrostatic charging	< 2kV	ISO 6356
Impact sound protection ΔLW	17 dB	ISO 140-8
Thermal resistance	0,06 m ² .K/W	ISO 8302
Slip resistance	> 0,3 Machine direction	EN 13893
	> 0,3 Crossdirection	EN 13893
Flammability	Cfl,s1 (Glued)	EN 13501-1
Prodis-ID (GuT)	DDA1EADD	www.pro-dis.info
AbZ Nr.	Z-156.601-703	

Floorsymbols



Certificates

EN 14041
CE
Reaction to fire: Cfl,s1 (Glued)
Slip resistance: DS
DOP: 1061#118LF00 Textile Floorcovering EN1307



Vebe Floorcoverings b.v. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system (according ISO 9001). The tests have been carried out according to the prescribed standards.