



spoltex



# Symphony

1/10" scroll	1/10" scroll	1/10" scroll	1/10" scroll
100% polyamid	100% polyamide	100% Polyamide	100% polyamide
<b>podklad</b> Ultratex	<b>dossier</b> Ultratex	<b>rücken</b> Ultratex	<b>backing</b> Ultratex
<b>výška vlasu</b> ± 6 mm	<b>hauteur du velours</b> ± 6 mm	<b>polhöhe</b> ± 6 mm	<b>pile height</b> ± 6 mm
<b>celková výška</b> ± 10 mm	<b>hauteur totale</b> ± 10 mm	<b>gesamthöhe</b> ± 10 mm	<b>total height</b> ± 10 mm
<b>váha vlasu</b> ± 550 g/m <sup>2</sup>	<b>poids du velours</b> ± 550 g/m <sup>2</sup>	<b>polgewicht</b> ± 550 g/m <sup>2</sup>	<b>pile weight</b> ± 550 g/m <sup>2</sup>
<b>celková váha</b> ± 1.470 g/m <sup>2</sup>	<b>poids total</b> ± 1.470 g/m <sup>2</sup>	<b>gesamtgewicht</b> ± 1.470 g/m <sup>2</sup>	<b>total weight</b> ± 1.470 g/m <sup>2</sup>
<b>počet vaz. bodů/m<sup>2</sup></b> ± 205 000	<b>nombre de points/m<sup>2</sup></b> ± 205 000	<b>noppen/m<sup>2</sup></b> ± 205 000	<b>tuft density/m<sup>2</sup></b> ± 205 000
<b>instalační metoda</b> • Univerzální fixace • Celoplošné lepení	<b>pose préconisée</b> • Produit de maintien • Fixateur	<b>empfohlene verlegeart</b> • Universalifixierung • Wiederaufnahme Klebstoff	<b>installation method</b> • Release bond
<b>použití</b> • Třída 22: střední v domácnosti • Komfort: 2 • Použitelný na teplov. podl. topení • Hořlavost. E <sub>fl</sub> EN 13501-1	<b>utilisation</b> • Classe 22: Domestique modéré • Confort: 2 • Classement. feu E <sub>fl</sub> EN 13501-1 • Compatible avec sol chauffant • Résistance thermique: ISO 8302: 0.15 m <sup>2</sup> K/W	<b>einsatz</b> • Klasse 22: mittel • Komfort: 2 • Baust.klasse E <sub>fl</sub> EN 13501-1 • Geeignet f. Fussbodenheizung • Wdw. ISO 8302: 0.15 m <sup>2</sup> K/W	<b>usage</b> • Class 22: medium • Comfort: 2 • Fire resist. E <sub>fl</sub> EN 13501-1 • Suitable f. floorheating

