

QUALITY
ORDER CODE

DATE: **4/12/2018**
REPLACES: 20/06/2018

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

MINERVA SB
MIN

± 400
COLLECTION
1/10" CUT PILE

PIECE DYED

PA

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 650
± 1.750

± 4,0
± 6,0
± 244.280
± 39,40
± 62,00

±
±

± 25
PILE IN

✓
✓
✓
✓
✓
✓
✓
✓

5B1C6F6D

18/321
U3P3E1C0

Cl. 33
Commercial Heavy



LC2



Bfl-s1



