

TILBURG

| | | |
|------------------------------|--|---------------------------|
| Manufacturing process | Tufted | ISO 2424 |
| Gauge | 5/32" Loop | |
| Secondary backing | AB + Felt | ISO 2424 |
| Width | 400 cm, 500 cm | ± 1% EN 986 |
| Pile weight | approx. 380 gr/m ² | ISO 8543 |
| Total weight | AB : approx. 1383 gr/m ² Felt : approx. 1360 gr/m ² | ± 15% ISO 8543 |
| Pile height | approx. 3,5 mm | ISO 1765 |
| Total height | AB : approx. 6,0 mm Felt : approx. 6,5 mm | + 15% / -10% ISO 1765 |
| Number of knots | approx. 120.960 /m ² | + 10% / -7,5% ISO 1763 |
| Fire classification | AB : Efl (EN13501-1) Felt : Efl (EN13501-1) | EN 13501-1 |
| Light fastness | ≥ 5 | 105-B02 |
| Wearability | ≥ 4,5 | 105-X12 |
| Water fastness | ≥ 4,5 | 105-E01 |
| Thermal resistance | 0,120 m ² K/W | ISO 8302 |
| Sound insulation | 10,0 dB | ISO 10140 |
| GUT Nr. | AB : 6F1EF980 Felt : AAFD71A0 | |

Floorsymbols AB



Floorsymbols Felt



Certificates

EN 14041
22



Reaction to fire:
Efl (EN13501-1)

Slip resistance:
DS
AB
DOP: 1058-128910

Textile Floorcovering
EN1307

EN 14041
22



Reaction to fire:
Efl (EN13501-1)

Slip resistance:
DS
Felt
DOP: 1058-128911

Textile Floorcovering
EN1307



schützt UMWELT und
GESUNDHEIT





